




d ₁	Δ	M1455 ZA								D A T A	
			d ₃	d ₄	s		n min.	h ≈	Δ	 (kg/1000)	FRg (N)
1.5	±0.10	ZA1.5	1.40	6.0	0.25	3	1.5	0.6	±0.15	0.040	100
2.0		ZA2.0	1.85	6.5	0.25	3	1.5	0.6		0.042	150
3.0		ZA3.0	2.80	8.0	0.25	4	1.5	0.8		0.066	200
3.5		ZA3.5	3.30	8.2	0.25	4	2.0	0.9		0.104	210
4.0		ZA4.0	3.80	9.0	0.25	4	2.0	0.8		0.078	220
5.0	±0.12	ZA5.0	4.80	10.0	0.25	4	2.0	0.8		0.082	230
6.0		ZA6.0	5.80	11.0	0.25	4	2.5	0.8		0.094	240
7.0		ZA7.0	6.80	12.0	0.25	4	2.5	0.8		0.110	250
8.0		ZA8.0	7.75	13.0	0.25	4	2.5	0.8		0.112	250
9.0		ZA9.0	8.75	14.0	0.30	6	2.5	0.9		0.208	300
10.0	±0.15	ZA10.0	9.75	16.0	0.30	6	3.0	1.1		0.232	320
12.0		ZA12.0	11.70	18.0	0.30	6	3.0	1.1		0.255	350
14.0		ZA14.0	13.70	20.5	0.30	6	3.0	1.2		0.310	400
15.0		ZA15.0	14.60	23.0	0.50	8	3.0	1.6		0.750	600
16.0		ZA16.0	15.60	24.5	0.40	8	3.0	1.4		0.710	700
17.0	±0.15	ZA17.0	16.60	26.0	0.50	8	3.5	1.5	0.950	800	
18.0		ZA18.0	17.60	27.0	0.40	8	3.5	1.4	0.810	850	
19.0		ZA19.0	18.60	28.0	0.50	8	3.5	1.5	0.950	900	
20.0		ZA20.0	19.50	29.0	0.50	8	3.5	1.6	1.090	950	
22.0		ZA22.0	21.50	31.0	0.50	8	3.5	1.6	1.150	1000	
23.0	±0.15	ZA23.0	22.50	31.5	0.50	8	4.0	1.5	1.220	1050	
25.0		ZA25.0	24.50	34.0	0.50	8	4.0	1.6	1.490	1100	
28.0		ZA28.0	27.50	37.0	0.50	8	4.0	1.8	1.550	1200	
30.0		ZA30.0	29.50	40.0	0.50	8	4.0	1.8	1.630	1300	
35.0		ZA35.0	34.50	46.0	0.50	8	4.0	1.8	2.100	1400	
45.0	±0.15	ZA45.0	44.50	60.0	0.50	8	4.0	2.5	2.700	1500	

Part Number
Référéncie Teile Nummer Referencia de pieza

Tolerance
Tolérance Toleranz Tolerancia

Weight
Masse Gewicht Peso

Ring
Anneau/Circlips Ring Anillo

Groove
Gorge Nut Ranura

